



CHARACTERISTICS

- Silicone-free
- High elasticity
- Contains solvents
- Elastic sealant based on synthetic rubber
- Can be used in rain and on damp or slightly oily surfaces
- Weather-resistant, UV-resistant
- Can be painted over with most paints

APPLICATIONS

- Has an adhesive strength without primer on the majority of materials used in building and engineering industries such as treated wood, aluminium, abs, steel, stainless steel, anodised steel, hard PVC, glass, etc
- Waterproof sealing and repair of leaks and joints in roofs, gutters, downpipes, air ducts, PVC pipes,...
- Adheres to almost all substrates without primer, such as masonry, concrete, bitumen, plaster, wood, glass, metal (including copper) and many plastics.

TECHNICAL CHARACTERISTICS

Type of product	Synthetic rubber
Density (g/ml)	0.95
Consistency	Pasta
Application temperature	+5°C - +40°C
Curing system	Evaporation of the solvent
Character	Elastic
Skin forming time at 23°C and 50% R.H. (min.)	15
Shore A hardness: ISO 868	25
Maximum permissible deformation: ISO 11600	25%
Modulus at 100% elongation: ISO 8339 (N/mm ²)	0.5
Shelf life of unopened product	24 months
Storage conditions	Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

12 x cartridge 290ML/box - 1200 pieces/pallet
Black

METHOD OF USE

Preparation

- The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary.
- Smooth surfaces may be wet, porous ones should be dry.

Application

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

- Apply the product from the cartridge or foil packaging with a manual or pneumatic caulking gun.
- The size and shape of the joint is very important. Avoid thin joints.

Tooling

- Smooth surface before skin formation with Perfect Joint Tooling Agent and/or the Perfect Joint Tool.

Paintable

- Given the wide variety of paint types available, it is recommended to test the compatibility of the sealant/adhesive with the paint in advance.
- Alkyd paints might require an extended drying time.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

POINTS OF ATTENTION

- Not suitable for use on PE, PP, PA, PTFE (Teflon).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply