



1213



2538

Tremco CPG Netherlands B.V
Vlietskade 1032
NL-4241 Arkel

14

22

GS241-20140517
illbruck.com/dop/GS241

EN 15651-1, -3: 2012

Non-structural sealant for joints for interior and exterior application
(intended for use in cold climates)

Non-structural sealant for sanitary joints

- Type F-EXT-INT-CC 12.5E, Type S XS1

- Conditioning: Method A

- Substrate: Aluminium, Glass

REACTION TO FIRE	Class E
-------------------------	---------

RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH	NPD
---	-----

WATER TIGHTNESS AND AIR TIGHTNESS

- Resistance to flow	$\leq 3\text{mm}$
----------------------	-------------------

- Loss of volume	$\leq 20\%$
------------------	-------------

- Tensile properties (i.e. at maintained extension after immersion in water at 23°C)	NF
--	----

- Secant tensile modulus (-30°C)	$\leq 0,9 \text{ N/mm}^2$
----------------------------------	---------------------------

- Tensile properties at maintained extension (-30°C)	NF
--	----

MICROBIOLOGICAL GROWTH	1
-------------------------------	---

DURABILITY	Passed
-------------------	--------

NF = no failure according to ISO 11600

NPD = No performance declared